

WAENGI MESH - POLYESTER BASKI BEZLERİ - TEKNİK ÖZELLİKLER

| TİP / MESH NO | 1 | 2 | 3 | 4 | 5 | 6 |
|---------------|----------------------------|-------------------------------|--------------------|------------------------------|--------------------|------------------------------|
| | Mesh Açıklığı | İp Kalınlığı | Eleme Sathı | Kalınlık | Ağırlık | Teorik Mürekkep Hacmi |
| | Mesh Opening (µ-mikron) | Thread Diameter (µ-mikron) | Open Area (%) | Mesh thickness (µ-mikron) | Weight (g/m2) | Th. Ink Volume (cm3/m2) |
| 24-120 | 296 | 120 | 50,6 | 210 | 81 | 106 |
| 32-70 | 245 | 70 | 60,5 | 107 | 36 | 65 |
| 43-80 | 145 | 80 | 41,5 | 125 | 62 | 52 |
| 48-70 | 130 | 70 | 42,3 | 108 | 60 | 46 |
| 54-64 | 113 | 64 | 40,8 | 98 | 52 | 40 |
| 61-64 | 88 | 64 | 33,5 | 102 | 59 | 34 |
| 68-55 | 82 | 55 | 35,8 | 84 | 50 | 30 |
| 77-48 | 76 | 48 | 37,6 | 76 | 42 | 29 |
| 77-55 | 68 | 55 | 30,6 | 85 | 55 | 26 |
| 90-40 | 68 | 40 | 39,6 | 64 | 34 | 25 |
| 90-48 | 55 | 48 | 28,5 | 78 | 50 | 22 |
| 100-40 | 57 | 40 | 34,5 | 61 | 37 | 21 |
| 110-34 | 54 | 34 | 37,7 | 51 | 32 | 19 |
| 120-31 | 49 | 31 | 37,5 | 48 | 27 | 18 |
| 120-34 | 43 | 34 | 31,2 | 53 | 35 | 17 |
| 120-40 | 36 | 40 | 22,4 | 633 | 44 | 14 |
| 140-34 | 30 | 34 | 22 | 52 | 40 | 11 |
| 150-31 | 30 | 31 | 24,2 | 44 | 32 | 11 |
| 150-34 | 25 | 34 | 18 | 52 | 42 | 9 |
| 165-31 | 21 | 31 | 18 | 46 | 36 | 8 |
| 180-27 | 20 | 31 | 15,4 | 43 | 31 | 7 |

Stoktaki en ve renkler

Available widths and colours

| | 108/115 | 132/137 | 154/157 | 204/208 | 230/234 | 306/310 | |
|--------|---------|---------|---------|---------|---------|---------|-----|
| 24-120 | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y |
| 32-70 | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y |
| 43-80 | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y |
| 48-70 | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y |
| 54-64 | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y |

| | | | | | | | |
|--------|-----|------|-----|-----|-----|-----|----------------|
| 61-64 | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y |
| 68-55 | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y |
| 77-48 | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y |
| 77-55 | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y |
| 90-40 | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y |
| 90-48 | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y |
| 100-40 | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y |
| 110-34 | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y |
| 120-31 | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y |
| 120-34 | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y |
| 120-40 | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y |
| 140-34 | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y |
| 150-31 | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y (eff. 280) |
| 150-34 | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y (eff. 280) |
| 165-31 | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y | W+Y (eff. 280) |
| 180-27 | W+Y | n.a. | W+Y | W+Y | W+Y | W+Y | n.a. |

Standard Colors: White (W) and Yellow (Y), other colors on request

Standard Length: 25 and 50 lin.mtrs (+/- 3 l.m.)

Nominal data subject to change, 15-06-07 / cle