



DZQ-600L



DZQ-600K

**Description:**

DZQ-600 series multi-functional vacuum gas flushing packaging machine not only can do the process of sealing, but also vacuum extraction or inert gas flushing after vacuum cycle. The function of model DZQ-600K is the same as that of model DZQ-600L, while the machine head of DZQ-600K is adjustable.

**Features:**

Multi-functional vacuum gas flushing packaging machine has chamberless design with double gas nozzles, so its application is not limited by the size of vacuum chamber.

**Application:**

DZQ-600 series multi-functional vacuum gas flushing packaging machine is suitable for package which has low demand on vacuum degree but high demand on the purity of inert-gas. Model DZQ-600L /S with double heating system is suitable for thick plastic or compound bag. The special sealing length 700, 800 or 1000 mm is available.

Note: For the powder smaller than 100 meshes, the machine should be equipped with Helix Subside Filter for collecting powder in order to protect vacuum pump.

**Parameters:**

	DZQ-600L(S)	DZQ-600K
Voltage (V/Hz)	AC 220/50 380/50	
Sealing Power (W)	600 (1000)	
Motor power (W)	750	
Air Compressor Power (W)	1100	
Sealing Length (mm)	600 700 800 1000	
Sealing Width (mm)	10	
Distance from Sealing Center to Floor (mm)	1250	
Tilting Angle of Sealing Head (°)	-	90
Vacuum Pump Rate (m <sup>3</sup> /h)	20	
Film Thickness (Single Layer) (mm)	≤ 0.18	
External Dimensions (L×W×H) (mm)	800×900×1900	960×940×1800
Net Weight (kg)	255	230